

SD6 Series

Housings > Indoor> Recessed/Pendant Mount > 6-inch Dome





Features

- Metal back-box for plenum applications
- Functional design
- For indoor applications
- Recessed and pendant-mount options
- Accommodates fixed or PTZ cameras

The SD6 housings are available in both recessed and pendant mount options and are built with Wren's standard approach for simple installation. The units feature a plenum-rated metal back-box and the pendant-mount version utilizes standard 1.5-inch NPT for simple connections. Both models feature a 6-inch optically-correct dome and accept either fixed or pan-tilt-zoom cameras.

Dimensions





PRODUCT SPECIFICATIONS

General

Construction

Backbox Steel construction; black powder-coat Shroud (SDP6) High-Impact Polystyrene (HIPS)

Dome Optical-grade polycarbonate

Trim Ring ABS

Bracket Heavy-gauge steel; black power-coat finish

Weight (without camera)

SDR6 4.4lbs (2.0Kg) SDP6 5.4lbs (2.45Kg)

Models

SDR6CW-F Recessed-mount, 6" Clear dome and with White trim ring for Fixed cameras SDP6CW-F Pendant-mount, 6" Clear dome and with White trim ring for Fixed cameras

Supported Cameras

SDR6 and SDP6 accommodate fixed cameras with a Maximum Camera/Lens (MCL) length of 9"

Need a custom finish or custom design? Let us help. Visit us at www.wrensoltuions.com/custom



124 Wren Parkway - Jefferson City, MO 65109 - (800) 881-2249 - www.wrensolutions.com

Wren®, the Wren logo, and The Power to See Your Business are trademarks of Wren. The trademarks that are followed by ® are registered trademarks in the U.S. All other trademarks and/or registered trademarks mentioned herein are properties of their respective owners and are for reference purposes only. The use of such third party trademarks does not indicate any affiliation with or sponsorship of or by Wren. Copyright © 2015 Wren. All rights reserved.

Environmental

Ceiling Tile Support Kit

Accessories

Indoor

CTS6