WREN SOLUTIONS

PUBLIC VIEW MONITOR

10" IP

SPECIAL FEATURES

- VMS-based Video Recording Via Network
- Text Overlay "Recording In Progress" or "Welcome" Messages
- Flashing or Continuous Blue LED, Front Panel White LEDs (On, Off, Flashing, Motion Activated)
- Video Motion Detection, Audio Alert and/or Front Panel White LEDs After Motion Detection
- Comes with Remote Control
- Firmware Upgrade via SD Card
- Customer Logo and Audio Clips Loadable via SD Card
- Camera Defeat Alarm
- Face Detection Boxes (Neon Green, Front and Side Detection)
- · Auto-on



FEATURES

- HD Video Provides Exceptional Viewing and Forensic Details
- Attention Grabbing Features Deliver High-Deterrent Value
- Low Voltage for Simple and Cost-Effective Deployments
- UL Listed
- PoE or DC Powered



PRODUCT INFORMATION SHEET

Model Number	PVM10-B-2086-W
Display	10" LED Backlight
Resolution	1280 x 800
Aspect Ratio	16:9
Brightness	250 NIT
Contrast Ratio	800:1
Viewing Angle - W x H	170° x 170°
Response Time	30 ms
VESA Pattern	75 x 75
Dimensions - W x H x D	7.44 x 9.64 x 1.38 (in)
Weight	4.0 lbs (1.8 kg)
Construction	White Steel w/ Glass Front
Operating Temperature	32°F - 104°F (0°C - 40°C)
Image Sensor	1/2.9" Sony IMX323
Camera Resolution	1080p
Effective Pixels	1985 (H) x 1105 (V), 2.19 MP
Minimum Illumination	0.01 Lux / F1.2
Lens	3.6mm fixed
Shutter Speed	1/60—1/10,000 second
CERTIFICATIONS	UL, FCC, RoHs



124 Wren Parkway, Jefferson City, MO 65109 USA (800) 881-2249 · www.WrenSolutions.com



Video Format	H.264
S/N Ratio	39 dB
Compatibility	Vivotek, ONVIF
Input Voltage	PoE 802.3af or 12V DC
SD Card	OSD, Firmware & LOGO
Network	RJ45
Digital Output	2 Spring Terminals

ACCESSORIES

MMB0303	Monitor Mount, Wall, Articulating, VESA 75x100, Black
MM-PVM08GUX-W	Monitor Mount, Retail Gondola Uprights, VESA 75x75, White
MM-PVM08CWA-W	Monitor Mount, Retail Display Walls, VESA 75x75, White
MM-PVM07SCO-W	Monitor Mount, Self-Checkout Power Pole Mount, VESA 75x75, White
CM-S10-8-W	Ceiling Mount, Telescoping, Single, 5-8' length, VESA 75x75 White
CM-S10-17-W	Ceiling Mount, Telescoping, Single, 8-17' length, VESA 75x75, White
CM-S10-27-W	Ceiling Mount, Telescoping, Single, 10-27' length, VESA 75x75, White
CM-BB10-8-W	Ceiling Mount, Telescoping, Back-to-Back, 5-8' length, VESA 75x75, White
CM-BB10-2-17-W	Ceiling Mount, Telescoping, Back-to-Back, 8-17' length, VESA 75x75, White
CM-BB10-27-W	Ceiling Mount, Telescoping, Back-to-Back, 10-27' length, VESA 75x75, White
DCSP-CMSBB10	Drop Ceiling Support Plate, Use with a CM-BB10-x or CM-S10-x pole
CS-7	Unistrut, 7', Open Ceiling Framing Channel, White
PS-10PVM	Power Supply, Brick, 12VDC, 4A

Wren,® the Wren logo, and Hyperion® are trademarks of Wren. The trademarks that are followed by @ are registered trademarks in the U.S. All other trademarks and/or registered trademarks mentioned herein are properties of their respective owners and are for reference purposes only. The use of such third party trademarks does not indicate any affiliation with or sponsorship of or by Wren_Solutions. Copyright @ 2021 Wren Solutions. All rights reserved.