

EXTRA-LARGE MONITOR SERIES



FEATURES

- HD and 4K Resolution Provides Sharp Detail
- Commercial Grade for 24/7 Use
- Auto-on Feature Eliminates Re-setting Monitor After Power Failures
- 24VDC Input for Flexibility in Wiring
- UL Listed
- 24VDC Power Supply Included

PRODUCT SPECIFICATIONS

MODEL NUMBER	GVM32-0-3011-B	GVM43-0-3016-B	GVM55-0-3016-B
DISPLAY			
Panel	32" LED Backlight	43" LED Backlight	55" LED Backlight
Resolution	1920 x 1080	4K 3840 x 2160	4K 3840 x 2160
Aspect Ratio	16:9		
Brightness		300 NIT	
Contrast Ratio	3000:1	1000:1	1200:1
Viewing Angle - W x H	178° x 178°		
Response Time	18 ms	8 ms	8 ms
CONNECTIONS / POWER			
Input Voltage	24VDC		
Power Consumption	60 W	72 W	240 W
External Control	Tamper Resistance Lock		
HDMI	2 Inputs		
USB	1 Input		
CERTIFICATIONS	UL, CE, FCC Class B RoHS Compliant		

EXTRA-LARGE MONITOR SERIES

ACCESSORIES

MOUNT	DESCRIPTION
MMB0302	Articulating Wall Mount, VESA 75x200, Black
MMB0601	Ceiling Mount, Back-to-Back, 1.5" NPT, VESA 400x400 Black (used with a CM-XL-x Pole)
MMB0602	Ceiling Mount, Single, 1.5" NPT, VESA 400x400, Black (used with a CM-XL-x Pole)
MMB0603	Ceiling Mount, Single, 1.5" NPT, VESA 75-200, Black (used with a CM-XL-x Pole)
MMB0604	Ceiling Mount, Back-to-Back, 1.5" NPT, VESA 75-200, Black (used with a CM-XL-x Pole)
CM-XL-5-W	Telescoping Pole, 2-5.5' length, White (used with a MMB060x Ceiling Mount)
CM-XL-11-W	Telescoping Pole, 6-11' length, White (used with a MMB060x Ceiling Mount)
CM-XL2-21-W	Telescoping Pole, 8-21' length, White (used with a MMB060x Ceiling Mount)
DCSP-CMXL	Drop Ceiling Support Plate, use with a CM-XL-x Pole, White
CS-7	Unistrut, 7', Open Ceiling Framing Channel, White